


LITTLE GIANT LIFTER


The powerful range of the Little Giant Lifter is very dependable for lifting and moving slab form loads. The Little Giant Lifter integrates a spring-loaded latch that automatically releases once the slab is fully lowered to the ground. It comes in many different sizes and available with either white or black high quality natural rubbers.

CODE	LENGTH X WIDTH X HEIGHT IN (MM)	GRIP RANGE IN (MM)	W.L.L LBS (KG)
ALG50-W	8 5/16 x 7 3/16 x 14 9/16 (211) x (183) x (370)	9/16 - 1 15/16 (15 - 50)	2860 (1300)
ALG60-W	8 1/2 x 7 15/16 x 15 7/8 (216) x (202) x (403)	13/16 - 2 3/8 (20 - 60)	3300 (1500)
ALG75-W	8 1/2 x 8 5/8 x 15 7/8 (216) x (219) x (403)	1 3/16 - 2 15/16 (30-75)	3300 (1500)

*Little Giant Lifter comes with white rubber, please inform us if you need black rubber

STONE VACUUM LIFTER


Abaco Stone Vacuum Lifter is designed to lift smooth surfaced stones, powered by compressed air. It features robust construction with the ability to lift and to incline the stone slab. The product comes in 4 different sizes, please check specifications below to determine which size is best suited for your needs.

MODEL	LENGTH X WIDTH X HEIGHT IN (MM)			
SVL25	35 5/16 x 25 3/4 x 39 15/16 (897) x (654) x (1014)			
SVL50	41 3/16 x 55 1/2 x 61 5/8 (1046) x (1410) x (1565)			
SVL75	36 13/16 x 71 1/16 x 62 3/16 (935) x (1805) x (1580)			
SVL100	48 7/16 x 55 1/2 x 61 5/8 (1230) x (1410) x (1565)			

MODEL	W.L.L LBS (KG)	NO. OF VACUUM PADS	MINIMUM SLAB DIMENSION IN (MM)	INCLINATION
SVL25	550 (250)	1 pc	24 3/8 x 16 3/8 (620 x 415)	0o - 90o
SVL50	1100 (500)	2 pcs	44 1/8 x 24 3/8 (1120 x 620)	0o - 90o
SVL75	1650 (750)	3 pcs	51 1/16 x 24 7/16 (1320 x 620)	0o - 90o
SVL100	2200 (1000)	4 pcs	51 1/16 x 31 1/2 (1320 x 800)	0o - 90o



FORKLIFT BOOM



Designed for use on 7700 lbs (3.5 tons) forklift trucks, the Forklift Boom offers versatility with maximum visibility for the operator. When full extended, Forklift Boom reaches up to 135 13/16" (3450 mm).

MODEL	LENGTH X WIDTH X HEIGHT IN (MM)	MAX LOAD WHEN FULLY EXTENDED LBS (KG)	W.L.L. LBS (KG)
AFJ35	80 15/16 x 22 3/4 x 18 1/4 (2056) x (578) x (463)	1320 (600)	3520 (1600)
AFJ25	61 1/16 x 22 13/16 x 16 5/16 (1550) x (580) x (415)	1100 (500)	4400 (2000)

*Little Giant Lifter comes with white rubber, please inform us if you need black rubber

WORK TABLE



- Rubber lined sturdy Working Table.
- Built in brackets designed for user to create different work stations.
- Independent adjustable footing.
- Constructed with 18 gauge 2" x 2" (50 x 50mm) square tubing.
- Our Working Table is available with or without casters.

MODEL	LENGTH IN (MM)	WIDTH IN (MM)	HEIGHT IN (MM)	W.L.L. LBS (KG)
AWT7523	75 7/8 (1927)	23 15/16 (608)	37 15/16 - 40 9/16 (965 - 1030)	1320 (600)
AWT7523C	75 7/8 (1927)	23 15/16 (608)	39 1/8 - 40 9/16 (993 - 1030)	1320 (600)

WLL = WORK LOAD LIMIT

BUNDLE SLAB RACKS


Rack is designed to store bundles of marble and granite in your warehouse or slab yard. The Bundle Rack has a Total Weight Capacity between Poles of 24,000lbs (11,000kg). Each pole is 2" x 4" x 1/4" x 59" (50 x 100 x 6 x 1500mm), and each steel rail base is covered with an additional strip of wood to protect the slabs from chips and scratches.

MODEL	LENGTH IN (MM)	WIDTH IN (MM)	HEIGHT IN (MM)	NET WEIGHT LBS (KG)	CAPACITY 1 LBS (KG)	W.L.L. LBS (KG)
BSR010	118 9/16 (3012)	6 9/16 (166)	59 7/16 (1510)	638 (290)	18260 (8300)	55000 (25000)

Maximum Weight Capacity Between Poles

ONE STOP A-FRAMES


Ideal for transporting or storing Stone Slabs or Glass sheets at a job site or in a warehouse. Rubber padding can protect the material from damaging and scratching. Six ratchets can hold materials securely even at transportation. Slots for forklift are available for all four faces also lifting hooks are available for crane use. Each component is designed to be dismantled easily to make possible to pack this A-frame to transport to another place. Square tubular section provides high rigidity and light weight, consequently you can handle this A-Frame easily.

MODEL	LENGTH X WIDTH X HEIGHT IN (MM)	LIFTING WITH FORK INSERTS LBS (KG)	LIFTING WITH EYELETS LBS (KG)	ROLLING CAPACITY LBS (KG)	STATIONARY W/O CASTERS LBS (KG)
OSA9458	94 1/2 x 43 5/16 x 72 7/16 (2400) x (1100) x (1840)	5500 (2500)	5500 (2500)	4400 (2000)	8800 (4000)

Maximum Weight Capacity Between Poles

DOUBLE HAND CARRY CLAMPS


Abaco Double Handed Carry Clamps are designed to safely lift and transport stone slab without using a forklift truck. The fully vulcanized rubber pads provide added grip and prevent from damage to the slab. The weight of the slab exerts a sufficient clamping force for such a simple lifting device. By eliminating the use of a forklift truck, the Carry Clamps help users to work more efficiently works. You can use multiple Carry Clamps to move larger slab with ease.

(Sold in pair) * Single Hand carry clamps also available

MODEL	LENGTH X WIDTH X HEIGHT IN (MM)	GRIP RANGE IN (MM)	W.L.L. PER SET POUNDS (KGS)
ACC40	11 5/16 x 5 1/8 x 9 7/16 (288) x (130) x (240)	0 - 1 9/16 (0 - 40)	440 (200)